

 **Scratch-free**
Industrial Scratch Resistant Coating

 **Protection against shards of glass**
In case of breakage, the glass is held together

 **Crystal clear**
The view is not distorted

 **EN 356 certified**
International breakage certification

 **Security adhesive**
Considerably stronger than the adhesive of heat protection films


 **Manufacturer**
Hanita Coatings RCA, Israel

 **35 years of experience**
One of the longest-operating distributors in the industry

 **Protection against breakage**
Getting through the glass is significantly slower

 **UV protection**
Protects your health and your valuables

Level of protection



Safety with window films!

Tensile strength
28500 psi
197 N/mm²

Break strength
336 lbs/inch
59 N/mm

	Single pane
Total Solar Energy Rejected	18%
Visible Light Transmitted	87%
Visible Light Reflected Exterior	11%
Total Solar Energy Reflected	10%
Total Solar Energy Absorbed	12%
Total Solar Energy Transmitted	78%
UV Rejection	99%
U-Value	6,07

 **Warranty**
10 years

 **Interior/exterior**
Interior

 **Certification**
EN12600 1B1, EN356 P2A

 **Thickness**
300 microns

 **Sizes available**
1,52x20 m

 **Adhesive**
Double security adhesive

 **Layers**
Three